





The Patent Office Concept House Cardiff Road Newport South Wales NP10 800

I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.


Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.

Signed

Andrew Gersey

Dated

30 April 2003



Pàraits Act 1977 (Rule 16) THE PATENT OFFICE The
L Patent
1 3 DEC 2002 Office

1/77

The Patent Office

Request for grant of a pateNYPORT

(See the notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)

11'3 DEC 2002

Cardiff Road Newport South Wales NP10 800

1. Your reference

85272/12768/03

2. Patent application number

(The Patent office will fill in this part)
Full name, address and postcode of the or of

3. Full name, address and postcode of the or of each applicant (underline all surnames)

EASTMAN KODAK COMPANY 343 STATE STREET ROCHESTER NEW YORK 14650-2201 UNITED STATES OF AMERICA

Patents ADP number (if you know it)

If the applicant is a corporate body, give the country/state of its incorporation

NEW JERSEY

B BARKER

423020001

0229090.6

4. Title of the invention

DISPLAY PANEL

5. Name of your agent (if you have one)

"Address for service" in the United Kingdom to which all correspondence should be sent (including the postcode)

KODAK LIMITED PATENTS, W92-3A HEADSTONE DRIVE HARROW MIDDLESEX HA1 4TY

1498618001

Patents ADP number (if you know it)

6. If you are declaring priority from one or more earlier patent applications, give the country and date of filing of the or of each of these earlier applications and (if you know it) the or each application number

Country

Priority application number (if you know it)

Date of Filing (day / month / year)

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application

Number of earlier application

Date of filing (day / month / year)

8. Is a statement of inventorship and of right to grant a patent required in support of this request? (Answer 'Yes' if:

- a) any applicant named in part 3 is not an inventor, or
- there is an inventor who is not named as an applicant, or
- c) any named applicant is a corporate body. See note (d))

YES

Patents Form 1/77

 Enter the number of sheets for any of the following items you are filing with this form.
 Do not count copies of the same document.

Continuation sheets of this form

Description

Claim(s)

Abstract

•

Drawing(s) 1 + (

10. If you are also filing any of the following, state how many against each item.

Priority Documents

Translations of priority documents

Statement of inventorship and right to grant of a patent (Patents Form 7/77)

Request for preliminary examination and search (Patent Form 9/77)

Request for substantive examination (Patent Form 10/77)

Any other documents (please specify)

11. **I**/

I/We request the grant of a patent on the basis of this application.

Bake

Signature

12/12/01

Date

12. Name and daytime telephone number of person to contact in the United Kingdom

B BARKER

020 8424 5177

Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

Notes

- a) If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- b) Write your answers in capital letters using black ink or you may type them.
- c) If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- d) If you have answered 'Yes' Patents Form 7/77 will need to be filed.
- e) Once you have filled in the form you must remember to sign and date it.
- f) For details of the fee and ways to pay please contact the Patent Office.

Display Panel

Field of the Invention

5

10

This invention relates to the field of display panels used in exhibitions and the like where short term advertising is required.

Background of the Invention

Easily erected and dismantled short term displays are often required for use in exhibitions, stores and such like. These are typically constructed as an aluminium framework which folds easily and springs up, much like an umbrella, when erected. The framework is then clad with flexible panels of either photographic or ink-jet media. These panels are attached to the framework using magnetic strips or similar attachment means. The display panels are typically 81.3 cm (32 inches) wide. However they may be joined to form large displays.

15 Curved panels may be used for the ends of the display. Clip on lighting may also be supplied.

The display panels are typically formed as a laminated sandwich. The back of the media bearing the image is laminated with a material which is totally light opaque to prevent light from the back of the display degrading the image quality. An example of such a material is a polyester/aluminium sandwich. This laminate also adds stiffness to the finished product. The top laminate, typically a polyester acrylic, provides a robust, scratch resistant, non reflective surface. It also adds to the rigidity of the finished product.

Problem to be solved by the Invention

Laminating the media carrying the image is a time consuming additional step in producing a display panel. It is also a costly addition.

It is known for paper media to split through the paper fibres when the panels are handled. This leads to unsightly damage of the panel edges which also reduces the life of the product. Piping or tunnelling can also occur. This is when the laminate adhesive separates from the media. This may occur if the panels are rolled too tightly. Pressure sensitive adhesives are particularly prone to this.

30

.20

Summary of the Invention

5

10

15

20

25

30

It is an aim of the invention to provide a display panel which is not subject to the above mentioned problems.

According to the present invention there is provided a method of forming a display panel comprising the step of coating an opaque support layer with at least one image carrying layer, the support layer providing stiffness to the panel.

The image carrying layer may be an emulsion layer or an inkjet receiving layer. Preferably the opaque support layer is pre-coated with a gel coat. This can be textured to provide a non glossy characteristic to the surface of the panel. Preferably the image carrying-layer is also coated with a waterproof overcoat which is permeable but which becomes waterproof during drying. This gives the display panel a more robust surface.

The invention further provides a display panel comprising an opaque support layer coated with at least one image carrying layer, the support layer providing stiffness to the panel.

Advantageous Effect of the Invention

A display panel according to the present invention does not need to be laminated. As the lamination step is not required the time taken to produce the panel is reduced. Furthermore, there is no risk of the panel splitting or any risk of piping and tunnelling.

The display panel is also cheaper to manufacture than those known in the prior art since the cost of lamination is eliminated.

Brief Description of the Drawings

The invention will now be described, by way of example, with reference to the accompanying drawing, in which:

Figure 1 is a schematic cross-sectional view of a display panel in accordance with an embodiment of the invention.

Figure 1 illustrates a panel according to the invention.

The display panel illustrated in Figure 1 has four layers. However this is a preferred embodiment and, as described later, not all layers are essential to the invention.

The back layer 1 of the panel is made from an opaque material. A preferred option is a plastics material such as an opaque polymer or polyester. This totally light opaque layer can be directly coated with a photographic emulsion, gel coat or ink receiver layer.

It will be understood that the invention is not limited to a back layer formed of plastics. Other possible materials for the back layer 1 could be aluminium, Estar-TM, an-Estar/tungsten sandwich or a resin coated paper. These examples are not to be taken as limiting the invention.

The back layer could also be textured either due to roughening agents applied in the plastics or by embossing the surface, as in resin coating. When coated with the image receiving layer, such techniques could provide alternative surface finishes to change the reflective properties of the final image panel.

The second layer 2 is a gel coat. This layer is not essential to the invention. The gel coat 2 can be textured as an alternative way to give a non glossy characteristic to the display, i.e. it provides a matt surface. A matt surface is usually preferred for panels for display in European exhibitions. However it is known that it is sometimes preferred to have glossy displays. In these instances the panel would be manufactured without the gel coat 2 or with a smooth gel coat.

The third layer 3 in the embodiment illustrated is an emulsion layer. The third layer could alternatively be an ink receiver layer. At least one layer is provided. The third layer 3 carries the image to be displayed.

The fourth layer 4 is a waterproof overcoat. This layer is not essential to the invention. However a waterproof overcoat is desirable since the resulting panel would be more robust. It is possible for the waterproof overcoat to be coated, in a permeable state, as part of the emulsion pack. It is then converted into a waterproof state during processing or by a heat/pressure fusing process.

However it is also-possible-for-the-waterproof-overcoat-to-be-applied-after-image.

formation...

5

10

15

20

25

The panel according to the invention is manufactured using known coating techniques. The layer 1 of opaque material is directly coated with the image carrying layer 3. If a matt surface is required for the display panel the layer 1 is either textured or pre-coated with a gel coat prior to being coated with the image carrying layer. The gel coat, or alternative coating, is then textured as required. Finally, a waterproof layer 4 is coated onto the front of the image carrying layer 3. This waterproof layer 4 is permeable during processing but becomes waterproof on drying. Examples of waterproof coats can be found in US 6221546, US 6165653 and US 6479222

The display panel produced according to this coating method is ready to be used in exhibitions without any further processes being required. The panel has sufficient stiffness and flexibility to be used in the "pop up" frameworks described above.

Known coating techniques can be used to produce the display panel according to the present invention. No new equipment is needed. Using a coating technique to produce the display panel negates the requirement for the panel to be laminated. The display panel according to the invention has sufficient stiffness and opacity for the panel to be used without the lamination required by prior art techniques.

The invention has been described in detail with reference to preferred embodiments thereof. It will be understood by those skilled in the art that variations and modifications can be effected within the scope of the invention.

10

15

Claims:

1. A method of forming a display panel comprising the step of coating an opaque support layer with at least one image carrying layer, the support layer providing stiffness to the panel.

5

- 2. A method as claimed in claim 1 wherein the at least one image carrying layer is an emulsion layer.
- 3. A method as claimed in claim 1 wherein the at least one image carrying layer is an ink receiving layer.
 - 4. A method as claimed in claim 1, 2 or 3 wherein the support layer is formed of a plastics material.
- 5. A method as claimed in claim 1, 2 or 3 wherein the support layer is formed of aluminium.
 - 6. A method as claimed in any preceding claim wherein the opaque support layer is pre-coated with a gel coat.

- 7. A method as claimed in any of claims 1 to 6 including a further step of coating the at least one image carrying layer with a waterproof overcoat.
- 8. A display panel comprising an opaque support layer coated with at least one image carrying layer, the support layer providing stiffness to the panel.
 - 9. A panel as claimed in claim 8 wherein the at least one image carrying layer is an emulsion layer.
- 30 10. A panel as claimed in claim 8 wherein the at least one image carrying-layer is an ink-receiving-layer.

- 11. A panel as claimed in claim 8 wherein the support layer is a plastics material.
- 12. A panel as claimed in claim 8 wherein the support layer is aluminium.
 - 13. A panel as claimed in any of claims 8 to 12 wherein a gel coat is provided between the support layer and the at least one image carrying layer.
- 10 14. A panel as claimed in any of claims 8 to 13 including a waterproof overcoat coated onto the at least one image carrying layer.

Abstract

Display Panel

A display panel is formed by coating an opaque support layer with at least one layer carrying an image. The opaque support layer provides the necessary stiffness to the panel.

FIGI

